


/



/

Mini

Telcordia GR-468-CORE

RoHS

DWDM

VMUX

Telcordia GR-468-CORE
RoHS

		Common			Mini			
	nm	1510~1610		1260~1360&1510~1610				
		1:99	5:95	10:90	1:99	5:95	10:90	
1	dB	≤0.6	≤0.7	≤1.0	≤0.6	≤0.7	≤1.0	
	dB	≤0.3						
	dB	≤0.1						
	dB	≥45						

PD	μA/mW	≥7	≥40	≥70	≥7	≥40	≥70	PIN respond to the input port
	nA	<1						@-5v V _{r,25}
	pf	≤1.5			≤10			f=1MHz;V _r =5V
	MHz	>1000			>300			RL=50,5v,-3dB
	dBm	24	17	14	24	17	14	
	V	15						
	mA	10						
		mm	Φ5.5*28			Φ3.0*22		
			75*60*12(-1)			33*31*6(8)		
			75*60*15(-2)					
			53*40*10(2/4/5)					

TAPD-□-□-□-□-□-□-□-□

Pin Type

00: unbent 01 bent

Bracket Style

C: Φ5.5*28 M:Φ3.0*22

Connector

FC,SC,LC,MU/UPC,APC

Fiber Length

1:1.0m customer specify

Fiber Dia

09: Φ0.9mm 025: Φ0.25mm

Fiber Type

S: single mode fiber H: G.655 single mode fiber

Tap Ratio:

01:1/99 05:5/95 10:10/90

Wavelength:

1550:1510~1610nm 135:1310&1550nm

OPDM-

Connector

00: no connector

FC

SC

LC/UPC

APC

Fiber Length

00:adapter

1:1.0m

customer specify

Fiber Dia

09: Φ0.9mm

025: Φ0.25mm

Fiber Type

S: single mode fiber

H: G.655 single mode fiber

Tap Ratio:

01:1/99

05:5/95

10:10/90

Wavelength:

1550:1510~1610nm

135:1310&1550nm

Channel Number:

1:Single channel

4:4 channels

8:8 channels

Type:

C:Common type

M:Mini type